

Tiger N-Type 60TR

360-380 Watt

MONO FACIAL MODULE

N-Type

Positive power tolerance of 0~+3%


IEC61215(2016), IEC61730(2016)

ISO9001:2015: Quality Management System

ISO14001:2015: Environment Management System

ISO45001:2018

Occupational health and safety management systems



Key Features



Multi Busbar Technology

MBB solar cell adopts new technology to improve the efficiency of modules, offers a better aesthetic appearance.



PID Resistance

Excellent Anti-PID performance guarantee via optimized mass-production process and materials control.



Durability Against Extreme Environmental Conditions

High salt mist and ammonia resistance.



Hot 2.0 Technology

The N-type module with Hot 2.0 technology has better reliability and lower LID/LETID.




Enhanced Mechanical Load

Certified to withstand: wind load (2400 Pascal) and snow load (5400 Pascal).



POSITIVE QUALITY™
Continuous Quality Assurance

LINEAR PERFORMANCE WARRANTY





15 Year Product Warranty

30 Year Linear Power Warranty

0.4% Annual Degradation Over 30 years

Engineering Drawings




Packaging Configuration

(Two pallets = One stack)

36pcs/pallets, 72pcs/stack, 936pcs/ 40'HQ Container

Electrical Performance & Temperature Dependence



Mechanical Characteristics

Cell Type	N type Mono-crystalline
No. of cells	120 (6×20)
Dimensions	1692×1029×30mm (66.61×40.51×1.18 inch)
Weight	19.0 kg (41.89 lbs)
Front Glass	3.2mm, Anti-Reflection Coating, High Transmission, Low Iron, Tempered Glass
Frame	Anodized Aluminium Alloy
Junction Box	IP68 Rated
Output Cables	TUV 1×4.0mm ² (+): 290mm, (-): 145mm or Customized Length

SPECIFICATIONS

Module Type	JKM360N-6TL3 JKM360N-6TL3-V		JKM365N-6TL3 JKM365N-6TL3-V		JKM370N-6TL3 JKM370N-6TL3-V		JKM375N-6TL3 JKM375N-6TL3-V		JKM380N-6TL3 JKM380N-6TL3-V	
	STC	NOCT	STC	NOCT	STC	NOCT	STC	NOCT	STC	NOCT
Maximum Power (Pmax)	360Wp	268Wp	365Wp	272Wp	370Wp	276Wp	375Wp	280Wp	380Wp	283Wp
Maximum Power Voltage (Vmp)	34.19V	31.58V	34.34V	31.72V	34.49V	31.88V	34.63V	32.03V	34.77V	32.20V
Maximum Power Current (Imp)	10.53A	8.50A	10.63A	8.58A	10.73A	8.65A	10.83A	8.73A	10.93A	8.80A
Open-circuit Voltage (Voc)	41.80V	39.45V	42.05V	39.69V	42.30V	39.93V	42.55V	40.16V	42.77V	40.37V
Short-circuit Current (Isc)	11.23A	9.07A	11.33A	9.15A	11.43A	9.23A	11.53A	9.31A	11.63A	9.39A
Module Efficiency STC (%)	20.66%		20.95%		21.24%		21.53%		21.81%	
Operating Temperature(°C)	-40°C~+85°C									
Maximum System Voltage	1000/1500VDC (IEC)									
Maximum Series Fuse Rating	20A									
Power Tolerance	0~+3%									
Temperature Coefficients of Pmax	-0.34%/°C									
Temperature Coefficients of Voc	-0.28%/°C									
Temperature Coefficients of Isc	0.048%/°C									
Nominal Operating Cell Temperature (NOCT)	45±2°C									

*STC: Irradiance 1000W/m² Cell Temperature 25°C

AM=1.5

NOCT: Irradiance 800W/m² Ambient Temperature 20°C

AM=1.5

Wind Speed 1m/s